



Tabela Técnica dos Condutores com ou sem Costura

DIMENSÕES					
NOM.	EXTERNO mm	PAREDE mm	KG/m	GRAU	SCH
1/4"	13,72		0,49		10
		2	0,58		20
		2,25	0,64	STD	40
		3,02	0,8	XS	80
		3,3	0,85		160
3/8"	17,15	1,65	0,63		10
		2	0,75		20
		2,31	0,85	STD	40
		3,2	1,1	XS	80
		4,75	1,45		160
1/2"	21,34	2,11	1		10
		2,5	1,16		20
		2,77	1,27	STD	40
		3,73	1,62	XS	80
		4,78	1,95	XXS	160
		7,47	2,55		
3/4"	26,67	2,11	1,28		10
		2,5	1,49		20
		2,87	1,68	STD	40
		3,91	2,19	XS	80
		5,56	2,89		160
		7,82	3,64	XXS	
1"	33,40	2,77	2,09		10
		3	2,25		20
		3,38	2,5	STD	40
		4,55	3,24	XS	80
			4,24		160
		9,09	5,45	XXS	
1.1/4"	42,16	2,77	2,69		10
		3	2,9		20
		3,56	3,39	STD	40
		4,85	4,46	XS	80
		6,35	5,61		160



Tabela Técnica dos Condutores com ou sem Costura

DIMENSÕES					
NOM.	EXTERNO mm	PAREDE mm	KG/m	GRAU	SCH
		9,7	7,76	XXS	
1.1/2"	48,26	2,77	3,11		10
		3	3,35		20
		3,68	4,05	STD	40
		5,08	5,41	XS	80
		7,14	7,24		160
		10,16	9,55		
2"	60,32	2,77	3,93		10
		3,5	4,9	STD	20
		3,91	5,44	XS	40
		5,54	7,48		80
		8,74	11,12		160
		11,07	13,44		
2.1/2"	73,03	3,05	5,26	STD	10
		3,5	6	XS	20
		5,16	8,64	XXS	40
		7,01	11,41		80
		9,52	14,91		160
		14,02	20,4		
3"	88,90	3,05	6,46	STD	10
		4	8,37	XS	20
		5,49	11,29		40
		7,62	15,27	XXS	80
		11,13	21,35		160
		15,24	27,68		
3.1/2"	101,60	3,05	7,41	STD	10
		4	9,63	XS	20
		5,74	13,57		40
		7,62	8,08	XXS	80
4"	114,30	3,05	8,37		10
		4	10,88		20
		6,02	16,07	STD	40



Tabela Técnica dos Condutores com ou sem Costura

DIMENSÕES					
NOM.	EXTERNO mm	PAREDE mm	KG/m	GRAU	SCH
		8,56	22,29	XS	80
		11,13	28,32		120
		13,49	33,54		160
		17,12	41,03	XXS	120
5"	141,30	3,4	11,56		10
		5	16,81		20
		6,55	21,77	STD	40
		9,52	30,94	XS	80
		12,7	40,28		120
		15,88	49,11		160
		19,05	57,43	XXS	
6"	168,30	3,4	13,83		10
		5	20,13		20
		6,35	25,36	STD	
		7,11	28,26		40
		10,97	42,56	XS	80
		14,27	54,2		120
		18,26	67,56		160
		21,95	79,22	XXS	
8"	219,10	3,76	19,97		10
		6,35	33,31		20
		7,04	36,81		30
		8,18	42,55	STD	40
		10,31	53,08		60
		12,7	64,64	XS	80
		15,09	75,92		100
		18,26	90,44		120
		20,62	100,92		140
		22,22	107,88	XXS	
		23,01	111,27		160
10"	273,05	4,19	27,78		10
		6,35	41,76		20
		7,8	51,02		30



Tabela Técnica dos Condutores com ou sem Costura

DIMENSÕES					
NOM.	EXTERNO mm	PAREDE mm	KG/m	GRAU	SCH
		9,27	60,3	STD	40
		12,7	81,54	XS	60
		15,09	95,99		80
		18,26	114,73		100
		21,44	133,03		120
		25,4	155,12	XXS	140
		28,57	172,25		160
12"	323,80	4,19	33,03		10
		6,35	49,72		20
		8,38	65,19		30
		9,52	73,79	STD	
		10,31	79,71		40
		12,7	97,44	XS	
		14,27	108,94		60
		17,47	131,99		80
		21,44	159,88		100
		25,4	186,93	XXS	120
		28,57	208,03		140
		33,32	238,71		160
14"	355,60	6,35	54,69		10
		7,92	67,9		20
		9,52	81,25	STD	30
		11,13	94,55		40
		12,7	107,39	XS	
		15,19	127,51		60
		19,05	158,1		80
		23,82	194,89		100
		27,79	224,65		120
		31,75	253,56		140
		35,71	281,7		160
16"	406,40	6,35	62,64		10
		7,92	77,83		20
		9,52	93,17	STD	30



Tabela Técnica dos Condutores com ou sem Costura

DIMENSÕES					
NOM.	EXTERNO mm	PAREDE mm	KG/m	GRAU	SCH
		12,7	123,3		40
		16,66	160,12		60
		21,44	203,53		80
		26,19	245,56		100
		30,96	286,64		120
		36,53	333,19		140
		40,49	365,36		160
18"	457,20	6,35	70,6		10
		7,92	87,75		20
		9,52	105,1	STD	
		11,13	122,43		30
		12,7	139,21	XS	
		14,27	155,87		40
		19,05	205,83		60
		23,83	254,67		80
		29,36	309,76		100
		34,92	363,64		120
		39,67	408,45		140
		45,25	459,68		160
20"	508,00	6,35	94,46		10
		9,52	140,88	STD	20
		12,7	186,94	XS	
		14,27	209,5		30
		17,48	255,24		40
		24,61	355,02		60
22"	558,80	6,35	86,51		10
		9,52	128,95		20
		12,7	171,03	XS	30
		15,88	212,61		40
		22,22	294,02		60
		28,57	373,57		80
		34,92	451,13		100



Tabela Técnica dos Condutores com ou sem Costura

DIMENSÕES					
NOM.	EXTERNO mm	PAREDE mm	KG/m	GRAU	SCH
		41,27	526,7		120
		47,62	600,28		140
		53,97	671,88		160
24"	609,60	6,35	94,46		10
		9,52	140,88	STD	20
		12,7	186,94	XS	
		14,27	209,5		30
		17,48	255,24		40
		24,61	355,02		60
		30,96	441,78		80
		38,89	547,33		100
		46,02	639,58		120
		52,37	719,63		140
		59,53	807,51		160
26"	660,40	6,35	102,42		
		9,53	152,96	STD	
		12,7	202,85	XS	20
		17,48	277,14		
		19,05	301,29	STD	
28"	711,20	6,35	110,37		
		9,53	164,9	STD	
		12,7	218,76	XS	20
		15,88	272,29		30
		17,48	299,03		
		19,05	325,15		10
30"	762,00	6,35	118,33		
		9,53	176,84	STD	
		12,7	234,67	XS	20
		15,88	292,18		30
		17,48	320,93		
		19,05	349,02		
32"	812,80	6,35	126,28		



Tabela Técnica dos Condutores com ou sem Costura

DIMENSÕES					
NOM.	EXTERNO mm	PAREDE mm	KG/m	GRAU	SCH
		9,53	188,78	STD	
		12,7	250,58	XS	20
		15,88	312,07		30
		17,48	342,83		40
		19,05	372,88		
34"		6,35	134,24		
		9,53	200,71	STD	20
		12,7	266,49	XS	30
		15,88	331,97		40
		17,48	364,73		
		19,05	396,75		
36"		6,35	142,19		
		9,53	212,65	STD	
		12,7	282,4	XS	20
		15,88	351,86		30
		17,48	386,62		
		19,05	420,61	STD	
38"	965,20	6,35	150,15		
		9,53	224,59	STD	
		12,7	298,31	XS	
		15,88	371,75		
		17,48	408,52		
		19,05	444,48		
40"	1016,00	6,35	158,1		
		9,53	236,53	STD	
		12,7	314,22	XS	
		15,88	391,65		
		17,48	430,42		
		19,05	468,34		